



US005912434A

United States Patent [19][11] **Patent Number:** 5,912,434**Robinson**[45] **Date of Patent:** Jun. 15, 1999[54] **KENNY CLAMP**[76] **Inventor:** Wayne H. Robinson, 671 Teton Dr.,
Lothian, Md. 20711[21] **Appl. No.:** 08/939,658[22] **Filed:** Sep. 29, 1997[51] **Int. Cl.⁶** H02G 15/02; H02G 3/18[52] **U.S. Cl.** 174/78; 174/51; 174/65 R[58] **Field of Search** 174/78, 74 R,
174/65 R, 51, 151; 439/98, 99[56] **References Cited****U.S. PATENT DOCUMENTS**

2,704,357	3/1955	Johnson	174/65 R X
2,710,381	6/1955	Monson	174/51 X
3,009,128	11/1961	De Carlo	174/51 X
3,206,539	9/1965	Kelly	174/68.3

4,145,566 3/1979 Weingartner 174/65 R

4,151,363 4/1979 Nichols 174/65 R

4,209,661 6/1980 Pate et al. 174/65 R

5,513,513 5/1996 Suess et al. 72/409.1 R


5,594,202 1/1997 Tobias 174/65 R R

Primary Examiner—Kristine Kincaid*Assistant Examiner*—Chau N. Nguyen*Attorney, Agent, or Firm*—Robert Halper

[57]

ABSTRACT

A grounding electrode conductor passes through a metallic surface of a panel board and is connected to a bus bar provided in the panel board. The conductor is supported by a press sleeve connector mounted on the panel board. A clamp is used to contact and secure the conductor to the connector. Both the grounding electrode conductor and the connector are in conformance with the 1996 National Electrical Code.

6 Claims, 2 Drawing Sheets

U.S. Pat. No. 5,912,434
09/614707
07/12/00